

Blacklight

UVA Blacklight Biax™

Germicidal

Aquarium and Reptile

Quartz Heat

Airfield Lighting




GE imagination at work

PERFORMANCE **iN**
LIGHTING

Speciality Lamps


Wattage (W)	Volts (V)	Cap	Product Description + Code GE	Code PIL	Peak Wavelength (mm)	Life (h)	Length (mm)	Pack Qty
Blacklight Blue T5								
4	29	G5	F4W/T5/BLB-39882	39882	368	5.000	150	25
6	42	G5	F6W/T5/BLB-39883	39883	368	5.000	225	25
8	57	G5	F8W/T5/BLB-39884	39884	368	5.000	300	25



Blacklight Blue T8								
18	57	G13	F18/T8/BLB-88832	88832	368	12.000	600	25
36	103	G13	F36/T8/BLB-88833	88833	368	12.000	1.200	25



Blacklight Blue T12								
20	57	G13	F20W/T12/BLB-34747	34747	368	9.000	600	6
40	101	G13	F40W/T12/BLB-25618	25618	368	20.000	1.200	6



Black Light T8								
15	55	G13	F15WBL 350-16941	16941	350	7.500	450	25



Wattage (W)	Volts (V)	Cap	Product Description + Code GE	Code PIL	Initial UVA Irradiance ¹ (mW/cm ² @ 20 cm)	Peak Wavelength (mm)	Life (h)	Length (mm)	Pack Qty
UVA Blacklight Biax™-Internal Starter									
9	60	G23	F9BX BL G23-42935	42935	440	368	440	167	10
11	91	G23	F11BX BL G23-42936	42936	670	368	670	237	10
13.4	58	GX23	F13BX BL GX23-42937	42937	630	368	630	177.5	10



UVA Blacklight Biax™ D-Internal Starter									
26	105	G24d-3	F26DBX BL G24d-3-42938	42938	630	368	630	169.5	10



UVA Blacklight Biax™ L-External Starter									
24	87	2G11	F24BX BL 2G11-42939	42939	980	368	980	326.8	10
36	107	2G11	F36BX BL 2G11-42940	42940	1280	368	1.280	421.8	10
55	101	2G11	F55BX BL 2G11-42941	42941	1630	368	1.630	541.8	10




Wattage (W)	Volts (V)	Cap	Product Description + Code GE	Code P/L	UV Output (Watts)	Peak Wavelength (nm)	Life (h)	Length (mm)	Pack Qty
Germicidal T5									
4	29	Miniature Bi-pin	G4T5-15872	15872	0.8	254	6.000	150	24
6	42	Miniature Bi-pin	G6T5-15873	15873	1.7	254	6.000	226	24
8	57	Miniature Bi-pin	G8T5-11077	11077	2.3	254	8.000	302	24
11	37	Miniature Bi-pin	G11T5-29495	29495	2.2	254	8.000	226	24
16	50	Miniature Bi-pin	G16T5-16494	16494	3.2	254	8.000	302	24
39	107	Single-pin (Fa8)	G36T5-15874	15874	12	254	9.000	865	24
65	180	Single-pin (Fa8)	G64T5-15864	15864	18	254	7.500	1575	24
39	115	Single 4 pin end cap	G36T5/4P/SE-29503	29503	12	NA	8.000	845	24
65	250	Single 4 pin end cap	G64T5/4P/SE-29504	29504	25	NA	8.000	1556	24




Wattage (W)	Volts (V)	Cap	Product Description + Code GE	Code P/L	UV Output (Watts)	Peak Wavelength (nm)	Life (h)	Length (mm)	Pack Qty
Germicidal T8									
15	55	G13 Medium Bi-pin	G15T8-11078	11078	4.8		8.000	451	24
25	46	G13 Medium Bi-pin	G25T8-11082	11082	6.9		8.000	451	24
30	90	G13 Medium Bi-pin	G30T8-11080	11080	12.4		8.000	908	24
55	83	G13 Medium Bi-pin	G55T8HO-15875	15875	18		8.000	908	24



Wattage (W)	Volts (V)	Cap	Product Description + Code GE	Code P/L	UV Output (Watts)	Peak Wavelength (nm)	Life (h)	Length (mm)	Pack Qty
Germicidal T4 Biax									
5	35	G23 2-pin	GBX5/UVC G23-40695	40695	1.0		8.000	85	10
9	59	G23 2-pin	GBX9/UVC G23-40696	40696	2.4		8.000	145	10
11	89	G23 2-pin	GBX11/UVC G23-40700	40700	3.6		8.000	215	10



Wattage (W)	Volts (V)	Cap	Product Description + Code GE	Code P/L	UV Output (Watts)	Peak Wavelength (nm)	Life (h)	Length (mm)	Pack Qty
Germicidal T6 Biax									
13	59	GX23 2-pin	GBX13/UVC GX23-40703	40703	3.6		8.000	170	10
18	58	2G11 4-pin	GBX18/UVC/2G11-40704	40704	5.3		8.000	225	10
36	106	2G114-pin	GBX36/UVC/2G11-40705	40705	12		8.000	415	10
55	101	2G114-pin	GBX55/UVC/2G11-15885	15885	16.5		8.000	535	10



Wattage (W)	Cap	Product Description + Code GE	Code P/L	Additional Information	Lumen (lm)	CCT (K)	CRI (Ra)	Life (h)	Length (mm)	Pack Qty
T8 Aquarium and Reptile										
15	G13	F15T8 F&SA- 16965 /44212	16965 /44212	Fresh & Salt Aqua	700	10000	60	9.000	450	10/6
15	G13	F15T8 FA-16977	16977	Fresh Aqua	400	5000	70	7.500	450	10
15	G13	F15T8 SW- 16987 /44230	16987 /44230	Salt Water	210	-	-	7.500	450	10/6
15	G13	F15T8 REP-44239	44239	Reptile	400	6400	82	7.500	450	6
18	G13	F18T8 F&SA-44213	44213	Fresh & Salt Aqua	950	10000	60	10.000	450	6
18	G13	F18T8 FA-16979	16979	Fresh Aqua	600	5000	70	7.500	600	10
18	G13	F18T8 SW-44231	44231	Salt Water	430	-	-	9.000	600	6
18	G13	F18T8 REP-44240	44240	Reptile	550	6400	82	7.500	600	6
25	G13	F25T8 F&SA-16968	16968	Fresh & Salt Aqua	1350	10000	60	15.000	760	10
25	G13	F25T8 FA-16980	16980	Fresh Aqua	805	5000	70	7.500	761	10
25	G13	F25T8 SW-16991	16991	Salt Water	430	-	-	7.500	762	10
30	G13	F30T8 F&SA- 16969 /44218	16969 /44218	Fresh & Salt Aqua	1700	10000	60	15.000	910	10/6
30	G13	F30T8 SW- 16992 /44235	16992 /44235	Salt Water	540	-	-	7.500	910	10/6
30	G13	F30T8 REP- 17004 /44241	17004 /44241	Reptile	1100	6400	82	7.500	910	10/6
36	G13	F36T8 F&SA- 16970 /44219	16970 /44219	Fresh & Salt Aqua	2350	10000	60	15.000	1200	10/6
36	G13	F36T8 SW- 16995 /44236	16995 /44236	Salt Water	700	-	-	7.500	1200	10/6
36	G13	F36T8 REP- 17006 /44242	17006 /44242	Reptile	1250	6400	82	7.500	1200	10/6
38	G13	F38T8 F&SA-44220	44220	Fresh & Salt Aqua	2200	10000	60	15.000	1060	6
38	G13	F38T8 FA-16984	16984	Fresh Aqua	1320	5000	70	7.500	1060	10
38	G13	F38T8 SW-16999	16999	Salt Water	650	-	-	7.500	1060	10



Speciality Lamps

Wattage (W)	Volts (V)	Cap	Product Description + Code GE	Code P/L	CCT (K)	Life (h)	Length (mm)	Pack Qty
Quartz Heat								
500	120	Slv	QH500T3/CL-21788	21788	2400	5,000	223.8	12
500	120	R7S	QH500T3/CL/7-21787	21787	2400	5,000	220.5	12
1000	200-220	Slv	QH1000T3/CL-22355	22355	2400	5,000	351	12
1000	230-250	Slv	QH1000T3/CL-22357	22357	2400	5,000	351	12
1000	230-250	Slv	QH1000T3/CL/1-22358	22358	2400	5,000	301	12
1000	230	Slv	QH1000T3/2CL/HT-22365	22365	2400	5,000	351	12
1000	235	Slv	QH1MT3/CL/R/MS-235V-21377	21377	2500	5,000	483	12
1000	230-250	Slv	QH1000T3/CL-22357	22357	2400	5,000	351	12
1200	144	Slv	QH1200T3/CL-22531	22531	2450	5,000	223.8	12
1200	144	Slv	QH1200T3/CL/HT-22532	22532	2450	5,000	223.8	12
1600	200	Slv	QH1600T3/CL-22686	22686	2350	5,000	503	12
1600	230-250	R7S	QH1600T3/CL/7-22691	22691	2400	5,000	498.4	12
1600	230-250	Slv	QH1600T3/CL-22688	22688	2400	5,000	503	12
2000	230	Slv	QH2M/T3/1CL/HT-22789	22789	2450	5,000	303	12
2000	230-250	Slv	QH2M/T3/1CL/HT/VB-15551	15551	2450	5,000	303	12
2000	220-250	Slv	QH2MT3/CL/VB-18668	18668	2450	5,000	350.5	12
2000	230-250	Slv	QH2M/T3/CL/HT-22790	22790	2450	5,000	350.8	12
2000	230-250	CER	QH2MT3/CL/HT/R-12716	12716	2450	5,000	352.5	12
2500	460-500	Slv	QH2500T3/CL-22838	22838	2400	5,000	731	12
2500	460-500	R7S	QH2500T3/CL/7-22837	22837	2400	5,000	727	12
3650	480	Slv	QH3650/CL/5-10872	10872	2500	5,000	1057	6
3800	550-600	Slv	QH3800/CL-22875	22875	2500	5,000	1062	6
5000	575-625	Slv	QH5M/T3/1CL/HT-22900	22900	2500	5,000	731.8	12

Jacketed Quartz Heat

500	230-240	Special	HH 210 500W CLEAR 230-240V-20089	20089	2450	5,000	218	10
1500	230-240	Special	HH 451 1500W RUBY 230-240V-20092	20092	2450	5,000	348	10
2000	230-240	Special	HH 804 2000W RUBY 230-240V-20093	20093	2450	5,000	348	10

Infrared Quartz Heat – Ruby Slim

750	230-240	RX7s	QH 750W 230-240V Ruby Slim-40723	40723	2450	5000	202.8	10
1300	230-240	RX7s	QH 1300W 230-240V Ruby Slim-42740	42740	2450	5000	254	10

Wattage (W)	Volts (V)	Cap	Product Description + Code GE	Code PIL	Lumen (lm)	Life (h)	Length (mm)	Pack Qty
200	6.6A	Special 1" Ribbon Leads	Q6.6A/T4/5CL-23857	23857	5000	500	76	12
200	6.6A	D.C.Bay	Q6.6AT4/DCR-23860	23860	5150	500	64	12
200	6.6A	Scrw Term	Q6.6A/PAR56/3-33279	33279	NA	1000	114	12
300	20A	Mog End Pr GX16d	Q20A/PAR56/C-15482	15482	NA	500	127	12
499	20A	Scrw Term	Q20A/PAR56/3-23863	23863	NA	500	114	12
45	6.6A	Mycalex cap & Prefocus collar	AF6/2 6.6A 45W-88420	88420	760	600	54	100
100	6.6A	Mycalex cap & Prefocus collar	AF 6/5T 6.6A 100W-88417	88417	2100	600	60	100
200	6.6A	Mycalex cap & Prefocus collar	AF7/2 6.6A 200W-88413	88413	4800	600	54	100
45	6.6A	PK30d	Q6.6A45PK30d male-80583	80583	800	1000	13.5	10
45	6.6A	PK30d	Q6.6A45PK30d female-80587	80587	800	1000	13.5	10
100	6.6A	PK30d	Q6.6A100PK30d male-80584	80584	2700	1000	13.5	10
100	6.6A	PK30d	Q6.6A100PK30d female-80588	80588	2700	1000	13.5	10
150	6.6A	PK30d	Q6.6A150PK30d male-80585	80585	3600	1000	13.5	10
150	6.6A	PK30d	Q6.6A150PK30d female-80589	80589	3600	1000	13.5	10
200	6.6A	PK30d	Q6.6A200PK30d male-80586	80586	4800	1000	13.5	10
200	6.6A	PK30d	Q6.6A200PK30d female-80590	80590	4800	1000	13.5	10

Airfield Lighting